




PROFILE STORE PRO LED 12W 8323



PROFILE STORE PRO LED 12W


Painted aluminum, plastic

8321 3000K 8323 3000K

8322 4000K



PROFILE STORE PRO LED 18W 8326



PROFILE STORE PRO LED 18W

Painted aluminum, plastic

8325 3000K 8327 3000K

8326 4000K



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8321	12W LED	3000K	1000 lm	24°	≥ 80	~220-230 V, 50/60 Hz	☑	>0.5	IP20	30000h
8322	12W LED	4000K	960 lm	24°	≥ 80	~220-230 V, 50/60 Hz	☑	>0.5	IP20	30000h
8323	12W LED	3000K	930 lm	24°	≥ 80	~220-230 V, 50/60 Hz	☑	>0.5	IP20	30000h
8325	18W LED	3000K	1440 lm	24°	≥ 80	~220-230 V, 50/60 Hz	☑	>0.5	IP20	30000h
8326	18W LED	4000K	1700 lm	24°	≥ 80	~220-230 V, 50/60 Hz	☑	>0.5	IP20	30000h
8327	18W LED	3000K	1600 lm	24°	≥ 80	~220-230 V, 50/60 Hz	☑	>0.5	IP20	30000h

WHITE BLACK

